

COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
J.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State  Fee   
5. State Oil & Gas Lease No.

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE \*\*APPLICATION FOR PERMIT - \*\* (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL  GAS WELL  OTHER   
Name of Operator: Amerada Hess Corporation  
Address of Operator: Drawer D, Monument, New Mexico 88265  
Location of Well: UNIT LETTER F, 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 19S RANGE 37E NMPM.  
15. Elevation (Show whether DF, RT, GR, etc.): 3598' DF  
12. County: Lea  
10. Field and Pool, or Wildcat: Funice Monument G/SA

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

June 20, 1983 to June 22, 1983 - Pulled rods & pump. Checked top of fill in open hole at 3885' of 30' of fill. String shot Grayburg San Andres zone in open hole fr. 3800' to 3882' w/400 grains per ft. Ran pkr. & tbq. Tested tbq. to 2500#. Loaded annulus & press. to 500#. Acidized Grayburg San Andres zone in open hole fr. 3790' to 3885' w/3000 gal. 15% NE FE acid mixed w/165 gal. Checker-Sol & 165 gal. scale inhibitor using 1500# rock sant as diverter. Flushed w/145 bbls. water mixed w/5 gal. surfactant. Swabbed load. Re-ran tbq., pump & rods and resumed pumping.

July 6, 1983 & July 7, 1983 - Pulled rods & changed pumps and resumed pumping.

Test of 7-8-83: Pumped 5 b.o. & no water in 24 hrs. on 8-24" SPM.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. B. Fisher TITLE Supv. Adm. Ser. DATE 7-8-83

APPROVED BY OIL & GAS INSPECTOR DATE JUL 12 1983

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUL 11 1983

O.C.D.  
HORRS OFFICE