

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

FEB 21 1 17 PM '67

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-1428
7. Unit Agreement Name
8. Farm or Lease Name State "U"
9. Well No. 1
10. Field and Pool, or Wildcat Monument
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Oil & Gas Dual
2. Name of Operator Amerada Petroleum Corporation
3. Address of Operator P.O. Box 668 - Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER E 1980 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 19S RANGE 37E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3592' DF

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Loaded casing with oil and pulled tubing and packer. Perforated 5" casing opposite Grayburg zone with one 3/8" jet shot at each of the following depths: 3816', 3818', 3823', 3827', 3836', 3844', 3846'. Total 7 shots. Set ret. bridge plug at 3854'. Acidized perms. 3816' to 3846' w/1000 gals. 28% NE acid using ball sealers. Swab Tested. Sand oil fraced perms. 3816' to 3846' w/7500 gals. oil & 6000# 20-40 sand. Swab tested. Replaced 2-7/8" tubing with 3-1/2" tubing and replaced packer to repair leak between oil & gas zones. Resumed production. No change in producing status or well classification.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED B. J. Linney TITLE District Superintendent DATE 2-20-67

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: