

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-05787

5. Indicate Type of Lease
STATE FEE

6. State Oil & Gas Lease No.
B-1128-1

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL GAS WELL OTHER

7. Lease Name or Unit Agreement Name
North Monument G/SA Unit Blk. 16

2. Name of Operator
Amerada Hess Corporation

8. Well No.
4

3. Address of Operator
P. O. Box 840, Seminole, Texas 79360-0840

9. Pool name or Wildcat
Eunice Monument Grayburg San Andres

4. Well Location
Unit Letter D : 660 Feet From The North Line and 660 Feet From The West Line
Section 32 Township 19S Range 37E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <u>Convert to Injection Well.</u> <input checked="" type="checkbox"/>		OTHER: _____ <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
Permit No. WFX716
Plan to MIRU pulling unit & TOH w/rods. Remove wellhead, install BOP & TOH w/tbg. TIH w/bit, tag TD at 3920' & TOH. TIH w/RBP set below 3500' & load & test 6-5/8" csg. Install new injection wellhead. Re-install BOP. TIH w/retrieving head, latch onto RPB & TOH. Perforate csg. fr. 3753' - 3788'. Acidize perms. w/4375 gal. 15% NEFE HCL acid. TIH w/injection eqpt. & begin injection operations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE R. L. Wheeler, Jr. TITLE Admin. Svc. Coord. DATE 7-17-97
TYPE OR PRINT NAME R. L. Wheeler, Jr. TELEPHONE NO. 915 758-6778

(This space for State Use)
APPROVED BY Charles Perri OIL & GAS INSPECTOR DATE 8-4-97
CONDITIONS OF APPROVAL, IF ANY: