

RECORD OF DRILL-STEM AND SPECIAL TESTS

IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEYS WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO. Maximum deviation: 1 1/2 deg at 2457 by TOTCO

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 3950 FEET, AND FROM FEET TO FEET. CABLE TOOL WERE USED FROM FEET TO FEET, AND FROM FEET TO FEET.

PRODUCTION

DATE OF COMMENCEMENT 4-1-57 TO

OF. TOTAL PRODUCTION DURING THE FIRST 24 HOURS WAS 84 BARRELS OF LIQUID OF WHICH 100 %

WAS OIL; % WAS EMULSION; % WATER, AND % WAS

SEPARABLE AND CAVITY 36.2

GAS PRODUCTION DURING THE FIRST 24 HOURS WAS M.C.F. PLUS

WEIGHT OF LIQUID HYDROCARBON. SHUT IN PRESSURE LBS.

WEIGHT OF OIL SHUT IN

WEATHER RECORDS BELOW FORMATION TOPS (In Conformance With Geographical Section Of State)

SOUTHEASTERN NEW MEXICO

NORTHWESTERN NEW MEXICO

S. ARIZONA 1445	T. DEVONIAN	T. OJO ALAJO
T. SALT 1530	T. SILURIAN	T. KIRTLAND-FRUITLAND
G. SAND 2600	T. MONTOYA	T. FARMINGTON
T. YACER 2762	T. SIMPSON	T. PICTURED CLIFFS
A. F. TOWER 3020	T. McKEE	T. MENEZES
T. GIBBS 3593	T. ELLENDURGER	T. POINT LOOKOUT
T. GRAYSON	T. GR. WASH	T. MANCOS
T. SALT PLAINS	T. GRANITE	T. DAKOTA
T. BURNETT	T.	T. MORRISON
T. DUNN	T.	T. PENN.
T. TUBBS	T.	T.
T. ARIZONA	T.	T.
T. PERMIAN	T.	T.
T. SALT	T.	T.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	1445	1445	Red Shale				
1445	1530	85	Anhydrite				
1530	2600	1070	Salt, Polyhalite, Shale				
2600	3020	420	Sand, shale, and anhydrite				
3020	3593	573	Dolo, shale, anhy				
3593	3950	357	Sand, anhy				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY OATH OR AFFIRM THAT THE INFORMATION GIVEN HEREWITH IS A COMPLETE AND CORRECT RECORD OF THE WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

June 10, 1957

(DATE)

COMPANY OR OPERATOR Humble Oil & Refining Company ADDRESS Box 2347, Hobbs, N.M.

NAME J.B. Van Shuren POSITION OR TITLE Agent