

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 4, 1955
(Date)

Hobbs, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Humble Oil & Refining Company
(Company or Operator)

New Mexico State AG
(Lease)

Wentley Drilling Company
(Contractor)

Well No. 1 in the SW 1/4 SW 1/4 of Sec. 1

T. 20-S, R. 37-S, NMPM, Undesignated Pool, Lea County.

The Dates of this work were as follows: 4-2 to 4-3-55

Notice of intention to do the work (was) ~~approved~~ submitted on Form C-102 on 1-10, 1955,
(Cross out incorrect words)

and approval of the proposed plan (was) ~~approved~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 167 joints 5-1/2-inch casing, 6914.40 feet, set at 6925 feet. Cemented with 306 sacks regular cement with 12% and 100 sacks regular neat. Plug on bottom at 11:00 A.M., 4-3-55. Scratchers from 6913 to 6863 feet, centralizers at 6909, 6829, 6122, 5996, 5204, and 5084 feet. Slurry weight on 12% gel cement 12.8#, on neat 15.5#.

Ran temperature survey after 6 hours, found top of cement at 2105 feet.

Tested casing with 1100# GNP for 30 minutes at 5:00 P.M., 4-3-55. Test O.K. No drop in pressure. Drilled plug and cement to top of shoe at 6924 feet. Ran Gamma ray and collar log and perforated casing from 6876 to 6900 feet with 4 bullets shots per foot.

Witnessed by J.E. Pozin Humble Oil & Refining Company Tool Pusher
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

A.G. Stanley
(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name J.M. Morgan

Position District Superintendent

Representing Humble Oil & Refining Company

Address Box 2347, Hobbs, New Mexico

(Title)

(Date)