

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

November 22, 1952 Monument, New Mexico
(Date) (Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation E. S. Adkins
(Company or Operator) (Lease)

Exploration Drilling Company Well No. 2 in the SW/4 SW/4 of Sec. 5
(Contractor)

T. 20-S, R. 37-E, NMPM, Monument-Blinbery Pool, Lea County.

The Dates of this work were as follows: November 21, 1952

Notice of intention to do the work (was) (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

5712' - Total Depth. LIME. Finished drilling 6-1/4" hole @ 8 AM, 11/17/52 - Ran Schlumberger's Surveys. Ran D.S.T. from 5655' to 5712' (See Log for results). Ran a total of 63 Jts of 5" OD casing as liner - Liner set @ 5665'. Top of Liner @ 3661'. Cemented W/160 Sx regular cement. Pumped plug to 5536' @ 1 AM, 11/19/52. Max press. 1500#. Cemented top of liner W/875 Sx cement - After WOC for 24 hours, Checked top of cement at 3024' - Drilled cement from 3024' to 3661 - at top of liner - Tested casing W/1500# for 1/2 hour - no pressure drop. Drilled 3' cement in top of 5" Liner. Drilled float shoe @ 5665 - washed to bottom @ 5712'. Open hole from 5665' to 5712'. Continued W/completion operations -

Witnessed by E. E. Shirley Amerada Petroleum Corporation Farm Bows
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION
Ray Quakray
(Name)
(Title) (Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.
Name: *D.C. Cassel*
Position: District Superintendent
Representing: _____
Address: _____