

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

1954 APR 7 AM 9:57

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 1, 1954
(Date)

Monument, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation
(Company or Operator)

E.S. Adkins
(Lease)

McVay & Stafford Drilling Co., Well No. **3** in the **SW**/₄ **SW**/₄ of Sec. **5**
(Contractor)

T. **20-S**, R. **37-E**, NMPM, **Monument-Blinbery** Pool, **Lea** County.

The Dates of this work were as follows: **3/29/54**

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)

and approval of the proposed plan ~~was~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3690' TD Lime & Sand - Finished drlg 8-3/4" Hole to 3690' @1:30 AM, 3/27/54. Ran Schlumberger Surveys. Ran a total of 119 jts of 7"OD Csg set @3690' W/100 sacks cement. Pumped plug & Open DV Collar, plug to 3499' @11:00 PM, 3/27/54 - Max press 800# - DV Collar set @3399'. After WOC 24 hrs. displaced mud W/salt water thru DV Collar behind 7"OD Csg and closed DV Collar W/1500#. Tested 7"OD Csg W/2000# - Held OK. Drid plug and DV Collar @3399'. Tested 7"OD Csg W/2000# - Held Ok. Drid cement from 3519' to 3690' and tested 7"OD Csg W/900# - Held OK. Started Drilling 6-1/4" hole from 3690' @6:30 PM, 3/29/54.

Witnessed by **G. F. Blount**
(Name)

Amerada Petroleum Corporation
(Company)

Farm Boss
(Title)

Approved: OIL CONSERVATION COMMISSION

G. J. Stanley
(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name *M. Smith*

Position **Foreman**

Representing **Amerada Petroleum Corporation**

Address **Drawer "D" - Monument, New Mexico**

(Title)

(Date)