

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

SEP 10 1953

Submit this report in **TRIPLICATE** to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

September 9, 1953

Hobbs, New Mexico

(Date)

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Cities Service Oil Company

Laughlin

(Company or Operator)

(Lease)

J. C. Grain Drilling Company

5

SW

SE

5

Well No. in the 1/4 of Sec.

(Contractor)

Lea

County.

T. **20S**, R. **37E**, **Undesignated** Pool, County.

9-5-53 through 9-7-53

The Dates of this work were as follows:

(Not required)

Notice of intention to do the work (was) (was not) submitted on Form C-102 on, 19.....
 (Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Laughlin #5 was drilled to a total depth of **5715'** in **lime**. Ran **5701.34'** (**182 1/2 jts**) of **5 1/2" OD 15.5# 8R J-55 SS Casing** set at **5713**. Ran **Rector "Fullbore" float shoe** on bottom and **Rector stage tool** at **4209'**. Cemented 1st stage w/**300 sacks** of which **200** was **posmix** containing **25 sacks** graded **pearlits** and **100 sacks** was **neat** on bottom. Circulated out **10 sacks** of first stage. WOC **8 hours**, then cemented 2nd stage w/**1000 sacks** **Posmix**, circulated out approximately **600 sacks**. Plug down on 2nd stage at **3:25 A.M.** **9-5-53**. Cement was allowed to set **48 hours**, **1000#** pressure was applied for **30 min** with no drop in pressure, test was **satisfactory**.

Witnessed by **C. M. Hartwell** **Cities Service Oil Company** **District Superintendent**
 (Name) (Company) (Title)

Approved: **OIL CONSERVATION COMMISSION**

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name **C. M. Hartwell**
 Position **District Superintendent**

Representing **Cities Service Oil Company**

Address **Box 97, Hobbs, New Mexico**

Engineer District 1

(Title)

SEP 10 1953

(Date)