

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

LEASE DESIGNATION AND SERIAL NO.

LC-031621-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

UNION TEXAS PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

1300 Wilco Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3568' DF

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Eumont (Queen)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 5, T-20-S, R-37-E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Abandon (Plug)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. September 6, 1978, MIRUSU & install BOP.
2. September 7, 1978, pulled 2-7/8" tubing out of hole.
3. September 8, 1978, circulated hole w/gelled mud. Set cement plugs as follows:
 - (a) 35 sx. plug of Class "C" from 2700' to 2900'.
 - (b) 25 sx. plug of Class "C" from 2400' to 2500'.
 - (c) 25 sx. plug of Class "C" from 1000' to 1100'.
 - (d) 10 sx. plug of Class "C" at surface.

Put in dry hole marker. Rig down service unit.

(Note: Well location in now ready for your inspection)

18. I hereby certify that the foregoing is true and correct

SIGNED Mloyd S. Houdyshell TITLE Production AnalystDATE September 15, 1978

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
MAR 6 1979
DATE
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side