

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Monument, New Mexico

May 4, 1936

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

Lambert

Well No. **1** in the

Company or Operator

Lease

NW 1/4 NW 1/4

of Sec. **6**

, T. **20**

, R. **37**

, N. M. P. M.,

Monument

Field,

Lea

County.

The dates of this work were as follows:

Notice of intention to do the work was (was not) submitted on Form C-102 on **May 1, 1936** 19

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

8-5/8" 28# 8-thd. New Electric welded casing was set in this well at 2310' and cemented by the Halliburton Method with 650 sacks of cement. 450 sacks through the casing and 200 through the Bordenhead.

DUPLICATE

Casing and fittings were tested with 1200# pump pressure and allowed to stand undisturbed for thirty minutes. No drop in pressure resulted. Cement plug was then drilled out of casing and the same test again applied and allowed to stand undisturbed for thirty minutes. No drop in pressure resulted, so drilling was resumed.

Witnessed by **Claud Cook** **Noble Drilling Co.** **Tool-pusher.**
Name Company Title

Subscribed and sworn to before me this **7**

I hereby swear or affirm that the information given above is true and correct.

day of **May**, 19 **36**

Name **J. A. Starnes**

Position **Farm Boss**

Representing **Amerada Petroleum Corporation**
Company or Operator

My Commission expires **10-24-39**

Address **Monument, New Mexico**

Remarks:

Name

Title

