EXICO OIL CONSERVATION COM SION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling opera-

ad sworn to before a notary public. See additional		ort by checking				o n.
		ore by enecking	Delow.			
EPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON F	REPAIRING W	ELL		1
EPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON F	PULLING OR C CASING			
EPORT ON RESULT OF TEST OF CASING SHUT-OFF	x	REPORT ON 1	DEEPENING V	WELL		
EPORT ON RESULT OF PLUGGING OF WELL						
	Mon	ument, New 1	Mexico		April Date	27,1936
IL CONSERVATION COMMISSION, anta Fe, New Mexico.						
entlemen:						
ollowing is a report on the work done and the results	obtained	under the hea	ding noted al	bove at the		
MERADA PETROLEUM CORPORATION		LAMBERT		TTT 11 3 7	1	
NW NW 1 Company or Operator NW NW 1 Of Sec. Monument Field, ne dates of this work were as follows:	_	Lease 20s		37 e		
Monument	Lea		, R		, N.	М. Р. М.,
Field,	Apri	1 26,1936.				County.
ne dates of this work were as follows:			Annil	95 1036	······	
otice of intention to do the work was (was cubit) subm	itted on	Form C-102 on	whire	DU, 1300.		
d approval of the proposed plan was (was not) obtain DETAILED ACCOUNT OF W	ined. (C					
197' of 122" new lapweld casing sacks of El Toro Cement. Hole was bailed dry and allowed 1200# pump pressure was applied stand undisturbed for thirty min cement plug was then drilled frowas again applied and allowed to was no drop in pressure. Drillin allowed to stand undisturbed for	was so to st to the nutes. Om inside standing was rone	one and interest in this to and undisture was relied the casil undisturbed resumed af hour and no	sell and or things look for this hole is water ha	thirty mi s and allo pressure pump pre- rty minutal been d accumul	with I nutes owed to The saure ses. I baile ated.	50 here
197' of 121" new lapweld casing sacks of El Toro Cement. Hole was bailed dry and allowed 1200# pump pressure was applied stand undisturbed for thirty min cement plug was then drilled frowas again applied and allowed to was no drop in pressure. Drillin allowed to stand undisturbed for	was so to st to the nutes. Om inside standing was rone	one and resumed af undisturbed the casing and undisturbed the casing and the casing are sumed as a f	sell and or things look for this hole is water ha	thirty mi s and allo pressure pump pre- rty minutal been d accumul	with I nutes owed to The saure ses. I baile ated.	.50 here i dry,

Remarks:

Name

REMARKS TO A TRANSPORT OF THE

. The constant constant a is the a -substituting a -substituting a -substituting a -substituting a

. .

to de la companya de