

NRDS OFFICE 000

SEP 17 PM 3:49

It is proposed to squeeze cement, perforate 7" casing and acid treat and recompleat as Salt Water Disposal Well as follows:

1. Pull tubing.
2. Run 2-7/8" tubing with cement retainer set at 5050'. Squeeze cement perforated interval from 5662-5674'. Pull tubing. WOC.
3. Perforate 7" casing from 4485-4505', 4530-4560', 4580-4600' and 4670-4690' with 4, 1/2" jet holes per foot.
4. Run 2-7/8" tubing with retrievable bridge plug at 4710' and parent packer at 4650'. Treat formation thru perforations in 7" casing from 4670-4690' with 1000 gallons 15% NE acid. Lower tubing and set bridge plug at 4615' and parent packer at 4470'. Treat formation thru perforations in 7" casing from 4485-4600' with 3000 gallons 15% NE acid. Pull tubing, bridge plug and parent packer.

CONFIDENTIAL

CA 3 MI VI 20 11

When a person is in a position of trust, it is their duty to act in the best interests of the community and to maintain the highest standards of integrity and honesty.

It is the policy of the Department to ensure that all personnel are held to the highest standards of conduct and that any breach of these standards will be dealt with appropriately. This includes the requirement that all personnel must act with integrity and honesty at all times.

The Department is committed to maintaining the highest standards of integrity and honesty, and to ensuring that all personnel are held to the highest standards of conduct. This includes the requirement that all personnel must act with integrity and honesty at all times.

The Department is committed to maintaining the highest standards of integrity and honesty, and to ensuring that all personnel are held to the highest standards of conduct. This includes the requirement that all personnel must act with integrity and honesty at all times.