

UNI] TEXAS PETROLEUM

FIELD: MONUMENT
 LEASE: BRITT WELL NO. 10
 DATE: 4-18-90 SPUDDED: 1-11-54 COMP. _____
 ELEV.: _____
 LOCATION: 1650' FEL & 330' FNL OF
SECTION 7, T-20S, R-37E
LEA COUNTY, NEW MEXICO

3029' OF 2 7/8" 6.5 #/FT J-55 EUE BRD TBG W/ TAC
 2905' & SN @ 3032'
 55 3/4" AND 66 7/8" RODS W/ 2 1/2" X 2" X 20' PUMP
 H-40
 13 3/8" 48* CSG. at 607' W/ 500 SX.
 17 1/4" HOLE TOC SURFACE (CIRC.)

PERF 8 5/8" @ 3304-05' & SQZ W/ 28 SX TRINITY INFERNO

8 5/8" 24 & 32* CSG at 3309' W/ 2000 SX. 1800 SX POSMIX
 200 SX NEAT
 11" HOLE TOC @ 720' (TEMP SURVEY) CSG DETAIL

2023' 8 5/8" 24# J-55
 1286' 8 5/8" 32# J-55

PERFS @ 5626-700'

5 1/2" 14 & 15.5* CSG. at 5719' W/ 313 SX.
 7 7/8" HOLE TOC @ 3280' (TEMP SURVEY) CSG DETAIL

697' 5 1/2" 14# GRADE B
 5022' 5 1/2" 15.5# JAPANESE
 GRADE A

T. KING

TD 5719'
 PBTD 5710'

RECEIVED
2001 JUL 11 AM 10:21
FBI NEW YORK
FEDERAL BUREAU OF INVESTIGATION
U.S. DEPARTMENT OF JUSTICE

RECEIVED
Hobbs
JUL 11 2001

(SUBMIT IN TRIPPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office **Las Cruces**
Lease No. **031621 (a)**
Unit **H. M. Britt**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	☒	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		S.A.U. setting & cementing casing	☒

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 6, 1954

Well No. **10** is located **330** ft. from **N** line and **1650** ft. from **E** line of sec. **7**

NW/4 NE/4 Sec. 7 (1/4 Sec. and Sec. No.)	20S (Twp.)	37E (Range)	N.M.P.M. (Meridian)
Mormont-Blinbury (Field)	Lee (County or Subdivision)	New Mexico (State or Territory)	

The elevation of the derrick floor above sea level is **3565** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Depth 5720'. Ran 152 jts. 5072.96' 5-1/2" OD 15.5 lb. J-55 and 22 jts. 696.83' of 14 lb. J-55.
 Set at 5719' with 210 sacks 64, 53 sacks stratacrete and 50 sacks neat cement.
 Indicated top of cement at 3280'. Plug down at 5:45 A.M. on 2-5-54. At 5:45 on 2-7-54 1000 lbs. pressure will be applied for 30 minutes for water shut-off test.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **ANDERSON-PRICHARD OIL CORPORATION**Address **BOX 2197****HOBBS****NEW MEXICO**By **Vincent Foster**Title **Jr. Engineer**

RECEIVED
2001 JUL 11 AM 10:21
EUROPEAN CENTRAL BANK
COMMUNICATIONS
UNIT

BUREAU OF LAND MGMT
ROOMELL OFFICE

2001 JUL 11 AM 10:21

RECEIVED

