

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)September 6, 1961  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation Bertie Whitacre Well No. 3 in F (Unit)  
(Company or Operator) Lease  
SE 1/4 NW 1/4 of Sec. 8, T. 20-S, R. 37-E, NMPM., Monument Pool  
(40-acre Subdivision)  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 3880'. PBTD 3849'. It is proposed to plug &amp; abandon as follows:

1. Attempt to load hole with water & pull tubing (Tubing is parted)
2. Provided hole will load & parted tubing is recovered, rerun tubing & spot plugs as follows:
  - a. Cement from PBTD at 3849' to 3650'. Mud from 3650' to 50' from surface. Cement from 50' to surface.
3. If hole will not load, set GI bridge plug on tubing at 3675', displace hole with mud, spot 5 sacks cement plug on top of BP, spot mud to 50' of surface, and 50' cement plug on top.
4. Install 4" marker, salvage equipment and clean up location.

cc: Anderson Prichard Oil Co., Jal, New Mexico., Amerada Pet. Corp., Drawer "D", Monument, N. M., Cities Service Oil Co., Box 97, Hobbs, N. M., Skelly Oil Co., Box 38, Hobbs, N. M., Trebol Oil Co., Box 778, Lovington, N.M., Continental Oil Co., Box 427, Hobbs, N. M., Sinclair O&G Co., 520 E. Bkwy., Hobbs, N.M., Pan American Pet. Corp., Box 68, Hobbs, N.M.

Approved....., 19.....  
Except as follows:Gulf Oil Corporation  
Company or OperatorApproved  
OIL CONSERVATION COMMISSION

Position Area Production Manager

Send Communications regarding well to:

By.....

Name Gulf Oil Corporation

Title.....

Address Box 2167, Hobbs, New Mexico