

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

RECEIVED

NOV 23 1953

MISCELLANEOUS REPORTS ON WELLS

OIL CONSERVATION COMMISSION

Submit this report in **TRIPLICATE** to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

November 20, 1953

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation

(Company or Operator)

Bertie Whitmire

(Lease)

Rife Drilling Co.

(Contractor)

Well No. 6 in the NW 1/4 NE 1/4 of Sec. 8

T. 20-S, R. 37-E, NMPM., Monument-Elmestrey Pool, Lea County.

The Dates of this work were as follows: November 17-19, 1953

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____, 19____.

(Cross out incorrect words)

and approval of the proposed plan ~~was~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 145 jts 5698' of 7" 20# & 23# N-80 & J-55 SS casing. Set & cemented at 5712' w/428 sacks cement in two stages with 10 centralizers & 34 scratchers at 4977' to 5711'. First stage w/186 sacks 4% Gel cement displaced w/mud. Opened DV tool at 4474'. Weatherford Petal Basket at 4504'. Circulated approximately 10 sacks cement. Second stage thru displacement type Howco DV tool at 4474' w/192 sacks 8% Gel & 50 sacks Neat cement on bottom. By Howco.

After waiting over 24 hrs., tested 7" casing w/1000# for 30 min. No drop in pressure. Drilled DV tool at 4474' and tested DV tool w/2000# for 30 min. No drop in pressure. Drilled cement from 5629' to 5717' and cleaned out to 5735'.

Witnessed by J. E. Sneed

(Name)

Gulf Oil Corporation

(Company)

Drilling Foreman

(Title)

Approved:

OIL CONSERVATION COMMISSION

S. J. Stanley

(Name)

Engineer District 1

(Title)

NOV 27 1953

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

Position Area Prod. Supt.

Representing Gulf Oil Corporation

Address Box 2167, Hobbs, New Mexico