

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO. 30-025-06023
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Lease Name or Unit Agreement Name Bertha J. Barber
2. Name of Operator CROSS TIMBERS OPERATING COMPANY	8. Well No. 8
3. Address of Operator 3000 N. Garfield, Suite 175 Midland, Texas 79705	9. Pool name or Wildcat Monument Blinebry
4. Well Location Unit Letter <u>D</u> : <u>330</u> Feet From The <u>North</u> Line and <u>330</u> Feet From The <u>West</u> Line Section <u>8</u> Township <u>20S</u> Range <u>37E</u> NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) <u>3,557' GR</u>	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <u>Workover</u> <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pull rods & tbg. Set RBP @ 5,350' above current Blinebry perfs fr/5556'-98'. Perforated fr/5156'-60' (16 holes). Acidize new perforations w/180 gals 15% NEFE HCL acid. Swab tested 100% wtr. Squeezed perfs fr/5156'-60' w/50 sx Class C cmt + additives. Drilled out sqz and tstd to 750 psig. Held OK. Pulled RBP @ 5350'. Acidized existing Blinebry perforations fr/5556'-98' with 2000 gals 15% Pental-200 HCL acid. Run tbg & rods. Pmp tstd 100% wtr. Pull rods & tbg. Set RBP @ 5341'. Re-sqz'd perfs fr/5156'-60' w/50 sx Class C cmt + additives. Drilled out sqz and tstd to 750 psig. Held OK. Pulled RBP @ 5341'. Run tbg & rods. Pmp tstd existing Blinebry perfs fr/5556'-98' w/high wtr cut. Rods parted. SD for eval. Repaired rod part & returned well to ppg on 6/28/96.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ray F. Martin TITLE Operations Engineer DATE 8/20/96
TYPE OR PRINT NAME Ray F. Martin TELEPHONE NO.

(This space for State Use)

APPROVED BY Ray F. Martin TITLE Operations Engineer DATE 8/20/96
CONDITIONS OF APPROVAL, IF ANY: