

Orig: & cc: OOC  
cc: VDA  
JTR  
F

(Form C-103)  
(Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

HOBBS OFFICE OOC

MISCELLANEOUS REPORTS ON WELLS

1954 JUL 9 AM 9:51

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

|   |  |   |                                     |                          |  |
|---|--|---|-------------------------------------|--------------------------|--|
| REPORT ON BEGINNING DRILLING OPERATIONS |  | REPORT ON RESULT OF TEST OF CASING SHUT-OFF | <input checked="" type="checkbox"/> | REPORT ON REPAIRING WELL |  |
| REPORT ON RESULT OF PLUGGING WELL       |  | REPORT ON RECOMPLETION OPERATION            |                                     | REPORT ON (Other)        |  |

July 8, 1954  
(Date)

Hobbs, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil & Gas Company  
(Company or Operator)

Bertha J. Barber  
(Lease)

Milhoan Drilling Company  
(Contractor)

Well No. 13-A in the SW 1/4 NW 1/4 of Sec. 8

Paddock

T. 20 S, R. 27 E, NMPM, Monument 111/ Pool, Lea County.

The Dates of this work were as follows: 7-2-54

Notice of intention to do the work ~~(was)~~ (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_, (Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Spudded 6-28-54

TD @ 990 - Set 13 3/8" OD casing @ 990 and cemented with 1,000 sacks of cement. Cement circulated to surface. Let set 48 hours and tested with 1,000# pump pressure for 30 minutes before and after drilling cement plug. No decrease in pressure. Resumed drilling.

Witnessed by Ira L. Wagner Sinclair Oil & Gas Co. Assistant foreman  
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

S. G. Stanley  
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name G. E. Miller

Position Dist. Supt.

Representing Sinclair Oil & Gas Co.

Address 520 East Broadway, Hobbs, N.M.