

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☒ Fee ☐

5. State Oil & Gas Lease No.  
**A-1212**

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name <b>SOUTH HOBBS (GSA) UNIT</b>
2. Name of Operator <b>AMOCO PRODUCTION COMPANY</b>	8. Farm or Lease Name <b>SOUTH HOBBS (GSA) UNIT</b>
3. Address of Operator <b>BOX 367, ANDREWS, TEXAS 79714</b>	9. Well No. <b>44</b>
4. Location of Well UNIT LETTER <b>J</b> <b>2310</b> FEET FROM THE <b>SOUTH</b> LINE AND <b>1650</b> FEET FROM THE <b>EAST</b> LINE, SECTION <b>4</b> TOWNSHIP <b>19S</b> RANGE <b>38-E</b> NMPM.	10. Field and Pool, or Wildcat <b>HOBBS-GSA</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3611 DF</b>	12. County <b>LEA</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

In an effort to increase productivity remedial work performed as follows:

- Ran cement bond log.
- Drilled out BP @ 4125'.
- Gcd open hole 4190 - 4210 w/ 250 gal 15%
- Perf 3958 - 4178 w/ 2350 PF.
- Acidized: 4115 - 78 w/ 2000 gal 15% NE HCl.
- 4070 - 4100 w/ 1500 " " " "
- 3958 - 4002 w/ 3000 " " " "

Evaluated - Prior - Amp 4 B0 + 1 BW 24 hr.  
after - " 22 B0 + 45 BW 24 hr.

TD- 4211  
PB- 4210

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Roy R. Yorkum TITLE ADMINISTRATIVE ASSISTANT

DATE OCT 28 1975

042- NMOC-#  
1-PLV  
1-SUSP  
1-RRY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE