

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico (Place) April 7, 1953 (Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Stanolind Oil and Gas Company
(Company or Operator) State A Tract 1 Well No. 7 in D (Unit)
NW $\frac{1}{4}$ NW $\frac{1}{4}$ of Sec. 4, T. 19-S, R. 38-E, NMPM., Bowers Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

The above well was completed in the Bowers Sand pay on 2-12-49 and at that time produced on pump at the rate of 8.97 barrels of oil in 24 hours. Since its completion, the production on this well has declined to nil. It is therefore our intention to plug and abandon this well as follows:

Spot a 25 sack cement plug in bottom of 5½" casing (approximately 2892' to 3092'), shoot off and pull approximately 425' of 5½" casing, spot 25 sack cement plug in 5½" casing stub, (425' to 625'). The 9-5/8" surface casing set at 444' and cemented to surface will be left in tact. A 20 sack cement plug will be set at the surface of the 9-5/8" casing. The interval between plugs will be filled with heavy mud.

The location will be leveled and a 4" abandonment marker will be erected to conform with existing New Mexico Oil Conservation Commission Regulations.

Approved _____, 19_____
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By Roy Yarrrough

Title _____

Stanolind Oil and Gas Company
Company or Operator

By Ralph L. Hendrickson

Position Field Superintendent
Send Communications regarding well to:

Name Ralph L. Hendrickson

Address Box 68, Hobbs, New Mexico