

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2038  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☐ OTHER- Injection  
Name of Operator  
Amoco Production Company  
Address of Operator  
P. O. Box 68, Hobbs, NM 88240  
Location of Well  
UNIT LETTER M 660 FEET FROM THE S LINE AND 660 FEET FROM  
THE W LINE, SECTION 4 TOWNSHIP 19-S RANGE 38-E NMPM.

7. Unit Agreement Name  
8. Farm or Lease Name  
South Hobbs (GSA) Unit  
9. Well No.  
53  
10. Field and Pool, or Wildcat  
Hobbs GSA  
12. County  
Lea

15. Elevation (Show whether DF, RT, GR, etc.)  
3604 DF

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
		OTHER <input type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to increase injectivity per the following method:

Drill out cement and retainer. Circulate out sand and pull bridge plug. Tag bottom of hole for fill. Run a gamma ray-temp. base survey from TD (4220') to 3900'. Run packer and tubing. Set packer at 3900'. Acidize with 2250 gals. 15% HCL mixed with 250 gals. Nalco's Visco 1176 tagged with radioactive Iodine at a rate of 2-3 BPM. Flush with 54 bbls. of water. Run gamma ray-temp. survey from TD to 3900'. Pull packer and tubing. Return well to injection.

0+4-NMOCD, H 1-Hou 1-Susp 1-CLF

15. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Cathy L. Ferman TITLE Assist. Admin. Analyst DATE 9-25-81  
Orig. Signed by  
Jerry Sexton  
APPROVED BY Dist 1, Supv. TITLE \_\_\_\_\_ DATE SEP 29 1981  
CONDITIONS OF APPROVAL, IF ANY: