

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
JUN 14 1948
RECEIVED

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within 10 days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

| | | | |
|--|----------|--|--|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL | | REPORT ON PULLING OR OTHERWISE ALTERING CASING | |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF | X | REPORT ON DEEPENING WELL | |
| REPORT ON RESULT OF PLUGGING OF WELL | | | |

Hobbs, New Mexico

Date

June 11, 1948

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Stanolind Oil & Gas Company H. D. McKinley NW/5 Well No. 8 in the _____
Company or Operator Lease

NW/4 of Sec. 5, T. 19-S, R. 38-E, N. M. P. M.,
Hobbs Field, Lea County.

The dates of this work were as follows: June 4-6, 1948

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on June 5 1948

and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On June 6, 1948 at 3:00 a.m. 30 hours had elapsed since running 3171' of 6-5/8" used casing in subject well and cementing with 800 sacks were used as intermediate string. At this time casing shut off was tested as follows: A pressure of 1000# was build up and held for 30 minutes, tested O.K. Cement plug was drilled and a pressure of 1000# was again built up and held for 30 minutes. This test, too, was O.K. Drilling operations were resumed. Elevation above sea level at derrick floor - 3633'. Well spudded May 21, 1948. Top of cement was located by Temperature Survey at 600' from surface.

Witnessed by Keith Hugett Stanolind Oil & Gas Company Farm Boss
Name Company Title

Subscribed and sworn before me this 11th

I hereby swear or affirm that the information given above is true and correct.

day of June, 1948

Name Ralph L. Hendrickson

R. Smith
Notary Public

Position Field Supt.

Representing Stanolind Oil & Gas Company
Company or Operator

My commission expires 2-23-50

Address Box "F" - Hobbs, New Mexico

Remarks:

APPROVED

JUN 14 1948

Date _____

Ralph L. Hendrickson
Name
Oil & Gas Inspector
Field Supt. Title