

MAY 12 1948
RECEIVED
HOBBS OFFICE

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

Place

May 10, 1948

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Stanolind Oil & Gas Company H. D. McKinley NW/5
Company or Operator Lease

Well No. 8 in NW/4

of Sec 5, T 19-S, R 38-E, N. M., P. M., Hobbs Field, Lea County.

The well is 660 feet ~~(N)~~ (S.) of the North line and 660 feet (E.) ~~(W)~~ of the West line of Section 5

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. _____ Assignment No. _____

If patented land the owner is H. D. McKinley Estate


Address _____

If government land the permittee is _____

Address _____

The lessee is _____

Address _____



AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: Rotary tools
to total depth of approximately 3250 feet.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: On file with Commission.

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
12 1/4"	9-5/8"	32.3#	NEW	350	Cemented	250
8-3/4"	6-5/8"	24#	USED	3250	Cemented	750

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3190 feet.

Additional information:

MAY 12 1948

Approved _____, 19____
except as follows: Cement must circulate
back to top of salt section on the
6 5/8" Csg.

Sincerely yours,

Stanolind Oil and Gas Company
Company or Operator

By Ralph L. Hendrickson

Position FIELD SUPT.

Send communications regarding well to

Name RALPH L. HENDRICKSON

Address BOX F, HOBBS, NEW MEXICO

OIL CONSERVATION COMMISSION,

By Ray Park
Title OIL & GAS