

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL OR RECOMPLETE

Notice must be given to the District Office of the Oil Conservation Commission and approval obtained before drilling or recompletion begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in **QUINTUPPLICATE**. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

(Place)

September 18, 1953

(Date)

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Gentlemen:

You are hereby notified that it is our intention to commence the (Drilling) (Recompletion) of a well to be known as

Stanolind Oil and Gas Company

(Company or Operator)

W. N. Terry Tract 3

(Lease)

Well No. 21

in E

(Unit)

The well is

located 1650 feet from the North line and 990 feet from the West

line of Section 9, T 19-S, R 36-E, NMPM.

(GIVE LOCATION FROM SECTION LINE)

Hobbs

Pool,

Lea

County

If State Land the Oil and Gas Lease is No.

If patented land the owner is W. N. Terry

Address Hobbs, New Mexico

We propose to drill well with drilling equipment as follows: Rotary tools to
total depth

The status of plugging bond is Blanket bond on file with Commission

Drilling Contractor Hewgley Drilling Company

408 Wilkinson-Foster Building, Midland, Texas

We intend to complete this well in the San Andres

formation at an approximate depth of 4300 feet.

CASING PROGRAM

We propose to use the following strings of Casing and to cement them as indicated:

Size of Hole	Size of Casing	Weight per Foot	New or Second Hand	Depth	Sacks Cement
<u>11"</u>	<u>8-5/8"</u>	<u>29.35#</u>	<u>Used</u>	<u>300</u>	<u>140 sx.</u>
<u>7-7/8"</u>	<u>5-1/2"</u>	<u>14#</u>	<u>New</u>	<u>4300</u>	<u>*</u>

If changes in the above plans become advisable we will notify you immediately.

ADDITIONAL INFORMATION (If recompletion give full details of proposed plan of work.)

*Two stage with DV tool set at approximately 1630' or top of salt section
1st Stage 105 sx. cement 4% gel plus 105 cu. ft. perlite with 110 sx. neat cement.
2nd Stage 100 sx. neat cement.

Approved SEP 18 1953, 19.....
Except as follows:

Sincerely yours,

Stanolind Oil and Gas Company
(Company or Operator)

By Keith J. Hendrickson

Position Production Foreman

Send Communications regarding well to

Name R. L. Hendrickson

Address Box 68, Hobbs, New Mexico

OIL CONSERVATION COMMISSION

By S. J. Stanley

Title Engineer District 1