

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

OF

MORA

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Shell Petroleum Corporation

State D

Company or Operator

Lease

Well No. 2

of Sec. 19

T. 19-S

R. 37E

N. M. P. M.

Monument

Field.

Lea

County.

Well is 1980 feet south of the North line and 660 feet west of the East line of Sec 19

If State land the oil and gas lease is No. 519 Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Shell Petroleum Corporation Address Houston Texas

Drilling commenced 5-25 1936 Drilling was completed 4-23 1936

Name of drilling contractor Oil Well Drilling Co Address Hobbs N M

Elevation above sea level at top of casing 3667 feet.

The information given is to be kept confidential until Not confidential 19

OIL SANDS OR ZONES

No. 1, from 3920 to 4002 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 2, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
12 1/2	50	8	SH	145	Baker				
9-5/8	36	8	Ingatow	1299	"				
7"	24	10	"	3743	"				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2	12 1/2	145	120	Halliburton		
11-3/4	9-5/8	1299	350	"		
8-3/4	7"	3743	275	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 4002 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 5-1-36, 19

The production of the first 24 hours was 3738 barrels of fluid of which 100 % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

E. J. Kinnetz Driller K. L. Cunningham Driller

Dick Schoeb Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 2

day of June 19 36

Patricia Mahoney
Notary Public.

Name R. J. Schuchle

Position District Engineer

Shell Petroleum Co.

