NEV/ MEXICO OIL CONSERVATION CO

SSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

of the Commission. Indicate natu	re of repor	rt by checking be	1011.		
REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON	REPAIRING W	ELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	-	REPORT ON I	PULLING OR O	THERWISE	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	x	REPORT ON I			
REPORT ON RESULT OF PLUGGING OF WELL					
Monument, 1	New Mexi	.co	Apri]	20, 193	7
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO.		Place		Date	
Gentlemen:					
Following is a report on the work done and the reaction Amerada Petroleum Corporation Company or Operator					in the
SE SW2 of Sec. 36	,		, R	36	, N. M. P. M.,
Monument Field,					
The dates of this work were as follows:					councy.
Notice of intention to do the work was [was net]				177 1077	10
		0			
DETAILED ACCOUNT OF			SULTS OB		dig .
	WORK I	OONE AND RE	SULTS OB		
8-5/8" 32# 8-Thd. New Seamless can	work ising was cks. th 12.0# th drop iseme tes	oone and result of 1200 pt of 1200 pt	well at a re and all esulted so	2318' and Lowed to the centure was a	stand ent was the
DETAILED ACCOUNT OF 8-5/8" 32# 8-Thd. New Seamless can the Halliburton Method with 600 sad Casing and fittings were tested with undisturbed for thirty minutes. No drilled out of the casing and the sand allowed to stand undisturbed for so the drilling was then resumed. Witnessed by H. D. JoCoy	work I sing was cks. th 12.0% c drop i same tes or thirt Bass I is Ref.	pump pressur rest of 1200 printing Co. Company hereby swear or a true and correct ame epresenting merical property and correct ame	well at a re and all esulted so mp presson drop in affirm that the Larkey upit.	cowed to the centre was a pressure Too	stand ent was the gain applie e resulted pl-pusher Title on given above
DETAILED ACCOUNT OF 8-5/8" 32# 8-Thd. New Seamless can the Halliburton Method with 600 sad Casing and fittings were tested with undisturbed for thirty minutes. No drilled out of the casing and the sand allowed to stand undisturbed for so the drilling was then resumed. Witnessed by H. D. JoCoy Name Subscribed and sworn before me this Notary Public	work I sing was cks. th 12.0% c drop i same tes or thirt Bass I is Ref.	pump pressur rest of 1200 printers. In pressure and correct ame true and correct ame position are researched.	well at a re and all esulted so amp presson drop in affirm that the Larky upit.	cowed to the centre was a pressure Too	stand ent was the gain applie e resulted pl-pusher Title on given above

State Geologist.

Title

Member Oil Conservation C'm's h