

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	Report on Setting Casing X

October 13, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation

State F

Well No. 5

in the _____

Company or Operator

Lease

SE 1/4 SW 1/4

of Sec. 36

T. 19S

R. 36E

N. M. P. M., _____

Monument-Paddock

Field, Lea

County.

The dates of this work were as follows: _____

October 10-13, 1948

Notice of intention to do the work was (~~was~~) submitted on Form C-102 on October 10, 1948 and approval of the proposed plan was (~~was~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

10255' Total Depth, Granite. Ran Schlumberger Survey, Calipers and Dip Meter. Ran total of 247 jts. of 5 1/2" OD, 17#, J-55 & N-80, R-3, 8-RT, SS Casing with 112 jts. of N-80 on bottom and 135 jts. of J-55 on top and set casing at 9978'. Cemented with 500 sx El Toro Cement mixed 2% Howcogel and 300 sx El Toro Regular Cement for a total of 800 sx. Plug pumped to 9894' at 6:15AM, 10-13-48, final pressure 2200#. Have 2 Larkin and 24 Baker Centralizers set between 9965' and 5130' and have 45 Weatherford Scratchers between 9977' and 5120'.

Witnessed by C. E. Telge

Amerada Petroleum Corporation

Farm Boss

Name

Company

Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

13th. day of October 1948

Name _____ *Don T. [Signature]*

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation

Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

[Signature]
Name _____
Title _____

RECEIVED
OCT 13 1948