

OIL CONSERVATION COMMISSION
 Santa Fe, New Mexico
MISCELLANEOUS REPORTS ON WELLS

RECEIVED
 AUG 27 1948
 DISTRICT OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	7"	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL		

August 26, 1948

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
 SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Gulf Oil Corporation

Graham State "F"

Well No. 5 in the _____

Company or Operator

Lease

SE SE

of Sec. 36

T. 19 S

R. 36 E

N. M. P. M.,

Blinbery

Field,

Lea

County.

The dates of this work were as follows: August 5, 1948 to August 24, 1948.

Notice of intention to do the work was (~~XXXXXX~~) submitted on Form C-102 on August 5, 1948

and approval of the proposed plan was (~~XXXXXXXX~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Perforations in casing from 5710' to 5745' were squeezed off with 100 sacks of cement and tested with 1400# pressure for 1/2 hour, tested OK. Drilled cement and casing tested again with 1400# pressure for 1/2 hour, tested OK. Bridging plug @ 6000' was drilled and casing tested a third time with 1500# pressure for 1/2 hour, tested OK. Hole was then bridged @ 7800' with Baker 3-B Model K retainer with 20 sacks of cement on top to 7700'. Casing was perforated from 7160' to 7277' with 4 shots per foot and well flowed 56 bbls in 24 hours through 22/64" choke, CP-525#.

Witnessed by H. L. Campbell Gulf Oil Corporation Drilling Foreman
 Name Company Title

Subscribed and sworn before me this 26th day of August 1948

I hereby swear or affirm that the information given above is true and correct.

Name E. J. Gallagher

Position District Sup't.

Representing Gulf Oil Corporation
 Company or Operator

Notary Public

My commission expires 10/1/48

Address Box 1667, Hobbs, New Mexico

Remarks:

H. L. Campbell
 Name
Notary Public
 Title