

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

**DISTRICT I**  
P.O. Box 1980, Hobbs NM 88241-1980  
**DISTRICT II**  
P.O. Drawer DD, Artesia, NM 88210  
**DISTRICT III**  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO.  
30-025-12480

5. Indicate Type of Lease  
STATE  FEE

6. State Oil & Gas Lease No.

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name  
North Monument G/SA Unit  
Blk. 14

1. Type of Well:  
OIL WELL  GAS WELL  OTHER

8. Well No.  
06

2. Name of Operator  
Amerada Hess Corporation

9. Pool name or Wildcat  
Eunice Monument G/SA

3. Address of Operator  
P. O. Box 840, Seminole, Texas 79360,

4. Well Location  
Unit Letter F : 1980 Feet From The North Line and 1980 Feet From The West Line  
Section 36 Township 19S Range 36E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

**SUBSEQUENT REPORT OF:**

PERFORM REMEDIAL WORK  PLUG AND ABANDON   
TEMPORARILY ABANDON  CHANGE PLANS   
PULL OR ALTER CASING   
OTHER: \_\_\_\_\_

REMEDIAL WORK  ALTERING CASING   
COMMENCE DRILLING OPNS.  PLUG AND ABANDONMENT   
CASING TEST AND CEMENT JOB   
OTHER: \_\_\_\_\_

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-20 thru 7-27-98

MIRU Tyler Well Svc. & TOH w/rods & pump. Removed wellhead, installed BOP & TOH w/tbg. TIH w/4-1/4" bit, tagged fill at 3917' & cleaned out fill to 3931'. Schlumberger ran GR log fr. 3921' - 2921'. Schlumberger perf. 5" liner using 3-1/8" expandable csg. gun w/2 SPF, total 73 shots, fr. 3794' - 3830'. American Fracmaster acidized csg. perfs. fr. 3794' - 3830' & 3845' - 3926' w/1000 gal. 15% HCL acid. Swabbed well. TIH w/2-7/8" tbg. set OE at 3905'. Removed BOP & installed wellhead. TIH w/pump & rods. RDPU, cleaned location & resumed producing well.

Test of 8-4-98: Prod. 114 B.O./D., 68 B.W./D., & 13 MCFGPD in 24 hours.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Roy L. Wheeler, Jr. TITLE Admin. Svc. Coord. DATE 8-7-98

TYPE OR PRINT NAME Roy L. Wheeler, Jr. TELEPHONE NO. 915 758-6700

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

5  
C