Submit 3 Copies
to Appropriate
District Office

APPROVED BY_

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

					
DISTRICT I P.O. Box 1980, Hobbs NM 88241-1980	OIL CONSERVAT		WELL API NO.	30.025 .2149 3 12483	
DISTRICT II Santa Fe, New Mexico 87504-2088 P.O. Drawer DD, Artesia, NM 88210		5. Indicate Type	30 023 E11100		
DISTRICT III				STATE 🛛 FEE 🗌	
1000 Rio Brazos Rd., Aztec, NM 87410			6. State Oil & Ga B-1167	i	
SUNDRY NOTICES AND REPORTS ON WELLS					
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name NORTH MONUMENT G/SA UNIT BLK.14		
1. Type of Well:					
OIL GAS WELL WELL	OTHER W	OTHER WATER INJECTION WELL		DER. 14	
2. Name of Operator			8. Well No.		
Amerada Hess Corporation			5		
3. Address of Operator P.O. DRAWER D, MONUMENT, NM 88265			9. Pool name or Wildcat EUNICE MONUMENT G/SA		
4. Well Location) Feet From The NORT	u	60	om The WEST Line	
Unit Letter E : 1980	Feet From The NOR1	H Line and 6	60 Feet Fro	om The WEST Line	
Section 36	Township 19S	Range 36E	NMPM	LEA County	
	10. Elevation (Show wi	hether DF, RKB, RT, GR, et	ic.)		
11. Check An	propriate Box to Indica	ate Nature of Notice	. Report, or	Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
	···	¬		- n <u>-</u> -	
PERFORM REMEDIAL WORK	PLUG AND ABANDON L	REMEDIAL WORK	X	ALTERING CASING	
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT		
PULL OR ALTER CASING		CASING TEST AND C	CASING TEST AND CEMENT JOB		
OTHER:		OTHER:			
STACK OUT TBG. PULLED TBG., 5-1/2" X 2-3/8" (PROFESSIONAL TESTERS. 2-3/8" L.H. ON-OFF TOO! WEDGED IN 31ST JT. AT 9 JTS. 2-3/8" TBG. & TOH & TOP JT. OF 2-3/8" TBG WEDGED IN 31ST JT. ALS		OFF TBG. & CSG. UNILOC MANDRAL THROUGH (SEMBLY. TOH W/112 JPKR. W/1.50" "F" PROJUCTOR FOR THE PVC LINED TBG. TOOLS & RECOVERED PINSPECTION. FOUND LING PVC LINER SECTION PVC LINER IN 3RD &	FLANGED & REM CARRIER BUT W TS. 2-3/8" SA FILE NIPPLE. "F" PROFILE N FOUND 3 PIECE: VC LINER PIEC INER BLISTERS THE SAME LEN 4TH JTS. TI	OVED INJ. AS UNABLE TO LTA PVC LINED MIRU IPPLE, 5-1/2" X S OF PVC LINER ES. TIH W/30 IN 28TH, 12TH, GTH THAT WAS H W/31 JTS.	
I hereby certify that the information above is	true and complete to the best of my know	wledge and belief.			
SIGNATURE LIKE	7. Gorvey	TITLE SR. STAFF ASSI	STANT	DATE01-24-96	
TYPE OR PRINT NAME TERRY. HAR				TELEPHONE NO. 505-393-2144	
(This space for State Use)	OVER LOWER CAY				
	MELO PER A			FEB 01 1995	

NMGSAU #1405 - CONTINUED (PAGE 2)

COMPLETE TBG. STRING HYDROTESTED TO 5,000#. RDMO PROFESSIONAL TESTERS. SET & GOT OFF PKR. AT 3,688'. CIRC. & DISPLACED WELLBORE W/180 BBLS. FRESH WATER & T-2264 CORROSION INHIBITOR MIXED. GOT ON PKR. & LANDED BREECH-LOC MANDRAL IN HANGER W/18,000# TENSION. ALLOWED FLUID TO WARM & EQUALIZE. REMOVED 6" 900 BOP. INSTALLED 7-1/16"-3M INJECTION WELLHEAD TREE & FLANGED UP INJ. LINE. PRESS. TESTED 7" CSG. & CHARTED 30 MIN. TEST TO 500#. WELL PASSED. NOTE: NMOCD NOTIFIED BUT NO WITNESS PRESENT FOR TEST. PRESSURED TBG. & BLEW PUMP OUT PLUG AT 2,400#. PUMPED 65 BBLS. AT 3.0 BPM DOWN TBG. TBG. ON VACUUM. TYLER WELL SERVICE & STAR TOOL RDMO. CLEANED LOCATION. INJECTING WATER ON 1/64" CHOKE SETTING & 669 BPD RATE.

