

*		

APPROVED

(SUBMIT IN TRIPLICATE)

DEC 5 1963

UNITED STATES OF AMERICA

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

J. L. GORDON
ACTING DISTRICT ENGINEER

Land Office New Mexico

Lease No. 02127-B

Unit EEF

DEC 5 1963

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	X
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 3, 1963

Lea Unit
S.W.D. Well No. 1 is located 1905 ft. from N line and 810 ft. from W line of sec. 12
NW 1/4 SW 1/4 Sec 12 20-S 34-E
(1/4 Sec. and Sec. No.) (Twp.) (Range)
Undesignated Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3665 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled to 3,899', ran 117 jts 5-1/2" J-55, 15.5 Weight csg to 3898'. Last setting depth includes Baker float shoe & collar 2.92'. Halliburton cemented w/600 sax Trinity Lite-Wate followed by 200 sax Trinity Reg. Plug down at 2:00 P.M. 11/27/63. Good cement returns to surface. W.O.C. 24 hrs. Tested csg w/1000# for 30 min, held OK.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Marathon Oil Company

Address Box 220 -

Hobbs, New Mexico

By Albert Mechler

Title Asst. Supt.