

APPROVED

Form 9-331a  
(Feb. 1951)


Budget Bureau No. 42-R358.4  
Approval expires 12-31-60.

SUB T. TOP  
MARCH 1963

(SUBMIT IN TRIPLICATE)

COPY TO G.C.  
HOBBS

Land Office \_\_\_\_\_  
Lease No. **MI 04063**  
Unit \_\_\_\_\_



E. W. STANDLEY  
DISTRICT ENGINEER

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

### SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 7, 1963

Well No. **1-10** is located **1900** ft. from **{N}** line and **1900** ft. from **{E}** line of sec. **10**

**NE/4 of Section 10** **T-20-S** **R-34-E** **N. M. P. M.**  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Wilcox** **Lee County** **New Mexico**  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **3649.9** ft.

#### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 2/28/63

Run 223' 3-5/8" 24# cog. set at 232' RT, cemented w/200 sms Regular w/21 SMS.  
Cement circulated. WOC 24 hrs.  
Pressure up to 1000# for 1 hr. and held pressure.

To 3700'. 213' 3-5/8" 24# cog. left in hole.  
Cement plug from 3150 to 3250' w/ 30 sms cement.  
Cement plug from 1450 to 1550' w/30 sms cement.  
Cement plug from 1560 to 1610' w/15 sms cement.  
Cement plug from 200 to 250' w/10 sms cement.  
15 sms. top of surface pipe.

Verbal approval given to Mr. Davis by Mr. Stanley on March 6, 1963.

\* Setting a regulation U.S.G.S. marker and clean up of the surface location.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Greathouse, Pierce & Davis**

Address **207 Midland Savings Bldg.**

**Midland, Texas**

By

Title

**PULLER**