

COUNTY	LEA	FIELD	Pearl-Queen	STATE	N.M.
OPR	CACTUS DRILLING COMPANY				MAP
	10 Aztec-State				
	Sec. 31, T-19-S, R-35-E				CO-ORD
	1980' fr N Line & 964' fr W Line of Sec.				
	Spud 4-3-64				
	Temp Abd. 5-25-64	CLASS			EL 3727 2
CSG & SX - TUBING	FORMATION	DATUM	FORMATION	DATUM	
	Sample:				
8 5/8" 100' 100	Queen 4641				
4 1/2" 5030' 200					
	LOG:				
	Yates 3580				
	Queen 4643				
LOGS EL GR RA IND HC A	Penr 4943				
	TD 5030'				

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Co. Tools	PROP DEPTH 5250'	TYPE
DATE		

F.R. 4-9-64
PD 5250' - Queen
Contractor - Co. Tools

4-6-64 Drlg. 3300'.
4-14-64 Drlg. 4860'.
Cored 4643-93', rec 48' dolo. & sd., w/scatt. show in sand.
Cored 4693-4702', rec 9' sd., w/NS.
4-21-64 TD 5030', prep to Ac.
Cored 4902-22', rec 20' sd. & dolo.
Cored 4987-5030', rec 43' being:
9' dense dolo.; 5' sd., w/fair show;
29' dns dolo.
Perf 4998-5004' W/4 SPF
4-27-64 TD 5030', PBD 4855', swbg.
Ac. 500 gals. 4998-5004'
Swbd dry.
Set BP @ 4975'
Perf 4898-4904' W/4 SPF

4-27-64 - continued -
Ac. 250 gals.
Frac 25,000 gals oil + 30,000# sd. 4898-4904'
Did not rec load.
Set BP @ 4855'
Perf 4668-73' W/4 SPF

5-4-64 TD 5030', PBD 4660', prep to P&A.
Swbd 100% water from perfs 4668-73'.
Squeezed perfs 4668-73' W/35 sx.
Drld out to 4660'
Perf @ 4656' W/3 shots
Swbd wtr

5-11-64 TD 5030', PBD 4660', prep to P&A.
5-18-64 TD 5030', PBD 4660', prep to P&A.
5-25-64 TD 5030', PBD 4660', TEMPORARILY ABANDONED.