

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN THIS DATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-03178

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL GAS WELL OTHER

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR

Greathouse & Pierce

8. FARM OR LEASE NAME

Federal

3. ADDRESS OF OPERATOR

204 V & J Tower, Midland, Texas 79701

9. WELL NO.

1-8

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

10. FIELD AND POOL, OR WILDCAT

660' FSL & 1980' FWL

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 3-T20S-R34E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3660' D. F.

12. COUNTY OR PARISH

Lea

13. STATE
N. M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spotted a 25 sx cement plug @ 9800'.
2. Spotted a 25 sx cement plug @ 4 1/2 casing stub @ 8503'.
3. Spotted a 25 sx cement plug @ base of 9-5/8 casing shoe @ 5032'.
4. Spotted a 25 sx cement plug @ 3300'-3400'.
5. Spotted a 25 sx cement plug @ 9-5/8 casing stub @ 1545'.
6. Spotted a 25 sx cement plug @ 13-3/8 casing shoe @ 572'.
7. Spotted a 10 sx cement plug @ surface w/marker.
8. Hole was loaded w/mud-laden fluids.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Agent

DATE

2/23/72

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
OCT 24 1972

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side