

FIELD EUNICE MANUFACTURING GSA	OPERATOR GULF	DATE 4/30/76
LEASE Bertie Whitwire	WELL No 9	LOCATION (H) 1780' FILL, 330' FEL SEC. 8-T 20S-R 37E

← 2 3/8" OD EVE TOG
w/ Guiberson "RM C-1" Packer @ 3419-3426' SM @ 3418'

9 5/8" - 36 #440 casing set at 1136' with 550 sx of 300 SX 47% Gel
250 SX Neat cement

3419 Hole size 12 1/4"
3426

Circulated

- 3500-3502' } Perfs Open
- 3534-3536' } w/ 2-0.41" JHPF
- 3560' CIBP (No Cement Cap)
- 3592-3594' Perfs w/ 2-0.41" JHPF
- 3602'
- 3612' - CIBP capped w/ 2 SX Cement
- 3620-3622' } Perfs
- 3623-3665' } w/ 2-0.41" JHPF
- 3695'
- 3700' CIBP
- 3715-3717' } Perfs
- 3731-3733' } w/ 2-1/2" JHPF
- 3743-3745' }
- 3756-3758' }
- 3763-3765' }

- 3770'
- 3774' Cement Retainer
- 3779-3781' } Perfs Squeezed w/ 500 SX
- 3789-3791' }
- 3804' - Cement Retainer
- 3811' Perfs Squeezed w/ 75 SX
- 3816'
- 3833'

7" - 23 # casing set at 3844' with 900 sx of cement

Total Depth _____' Hole size 9 3/4" stage ① - 75 SX Neat Circ. out DV Tool
 ② - 25 SX 16% Gel, 5% Salt, 0.2% ...
 followed by 100 SX Neat
 Calc TOC @ Surface