



**RECORD OF DRILL-STEM AND SPECIAL TESTS**

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

**TOOLS USED**

Rotary tools were used from Surface feet to 1262' feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
 Cable tools were used from 1262' feet to 3230' feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

**PRODUCTION**

Put to Producing November 2, 1964  
 OIL WELL: The production during the first 24 hours was 48 barrels of liquid of which 98.75 % was  
 was oil; \_\_\_\_\_ % was emulsion; 1 % water; and 1/2 % was sediment. A.P.I.  
 Gravity 32  
 GAS WELL: The production during the first 24 hours was \_\_\_\_\_ M.C.F. plus \_\_\_\_\_ barrels of  
 liquid Hydrocarbon. Shut in Pressure \_\_\_\_\_ lbs.  
 Length of Time Shut in \_\_\_\_\_

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy. <u>1253'</u>	T. Devonian _____	T. Ojo Alamo _____	
T. Salt <u>1458'</u>	T. Silurian _____	T. Kirtland-Fruitland _____	
B. Salt <u>2785'</u>	T. Montoya _____	T. Farmington _____	
T. Yates <u>2984'</u>	T. Simpson _____	T. Pictured Cliffs _____	
T. 7 Rivers <u>3220'</u>	T. McKee _____	T. Menefee _____	
T. Queen _____	T. Ellenburger _____	T. Point Lookout _____	
T. Grayburg _____	T. Gr. Wash _____	T. Mancos _____	
T. San Andres _____	T. Granite _____	T. Dakota _____	
T. Glorieta _____	T. <u>D. 3230'</u>	T. Morrison _____	
T. Drinkard _____	T. _____	T. Penn _____	
T. Tubbs _____	T. _____	T. _____	
T. Abo _____	T. _____	T. _____	
T. Penn _____	T. _____	T. _____	
T. Miss _____	T. _____	T. _____	

**FORMATION RECORD**

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	480	480	Red bed	1770	1820	50	Salt
480	655	175	Red bed and shells	1820	1885	65	Salt
655	795	140	Sand, shale	1885	1900	15	Anhydrite
795	1055	260	Red sand	1900	2665	765	Salt
1055	1185	130	Red Bed	2665	2680	15	Anhydrite
1185	1248	63	Red Shale	2680	2810	130	Anhydrite
1248	1262	14	Anhydrite, Salt, Shale	2810	2900	90	Anhydrite
1262	1295	33	Anhydrite and lime	2900	2995	95	Lime, sand, shale
1295	1340	45	Anhydrite	2995	3035	40	Lime
1340	1370	30	Lime	3035	3045	10	Lime, sand, shale
1370	1380	10	Anhydrite	3045	3055	10	Sandy shale
1380	1420	40	Salt, white	3055	3095	40	Lime
1420	1445	25	White	3095	2110	15	Sandy lime oil
1445	1520	75	Anhydrite	3110	3130	20	Sand
1520	1535	15	Red Shale	3130	3140	10	Lime
1535	1545	10	Salt	3140	3150	10	Sandy lime and shale
<del>1545</del>	1565	20	Anhydrite, Shale	3150	3180	30	Lime
1565	1605	40	Salt, Shale	3180	3205	25	Sandy Dolomite
1605	1640	35	Anhydrite, Shale, Salt, St.	3205	3210	5	Sand
1640	1690	50	Salt and Shale	3210	3225	15	Sandy Dolomite
1690	1755	65	Salt and Anhydrite	3225	3230	5	Sand Oil
1755	1770	15	Anhydrite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

*L. Earl Beal* Nov. 13, 1964  
 (Date)

Company or Operator Shoreline Exploration Co. Address 1117 Fort Worth National Bank Bldg.  
Fort Worth, Texas  
 Name \_\_\_\_\_ Position or Title Vice-President