

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424.

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.
LC-069944

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
LITTLE EDDY UNIT

8. FARM OR LEASE NAME

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
5-20-33 N.M.P.M.

12. COUNTY OR PARISH
LEA

13. STATE
N.M.

1. GIL WELL GAB WELL OTHER DRILLING

2. NAME OF OPERATOR
PAN AMERICAN PETROLEUM CORP.

3. ADDRESS OF OPERATOR
Box 68, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

14. PERMIT NO.
GGO FSL x 1984.9 FWL SEC 5 (UNIT N SE 1/4 SW 1/4)

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3565' R.D.B.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 5-19-66, 5 1/2" OD 17-20" N-80 BT, LT, +C Casing was set at 14,608' w/500 sk. Trinity Inferno neat Cement. Tested casing w/2600 PSI for 30 minutes, Test O.K. Drilled out to a depth of 14,895', No show of oil or gas. Set 100 sk. Cement plug from 14,895' to 14,395'. Perforated 11,600-595 w/2 1/2" SPF. BP set at 11,800'. Cemented thru perforations w/2350 sk. Cement.

We propose to perforate the Wolfcamp pay and test as discussed between our Mr. Smith and Mr. Brown.

RECEIVED
JUN 9 1966
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED _____

TITLE Area Supt.

DATE 5-2-66

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

APPROVED
JUN 9 1966
A. R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

5-2-66 JSGS-A
1-NSW
1-CUSP
1-RZY
1-PERFOR BASS
1-STATE LAND
1-US BORAX