

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER Dry		5. LEASE DESIGNATION AND SERIAL NO. NMD-62479
2. NAME OF OPERATOR Roger C. Hanka		6. IF INDIAN, ALLOTTEE OR TRIBE NAME None
3. ADDRESS OF OPERATOR 1102 Oil & Gas Building, Wichita Falls, Texas 76301		7. UNIT AGREEMENT NAME None
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FEL and 1980' FNL of the Section		8. FARM OR LEASE NAME U. S. Government
14. PERMIT NO. Ltr. dated 8-11-66		9. WELL NO. One
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3581' Gr.		10. FIELD AND POOL, OR WILDCAT Wildcat
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 3-20S-33E
		12. COUNTY OR PARISH Lee
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud Date: 8-16-66

Plugging Date: 8-22-66

Summary: Well was drilled to depth of 3460' (Driller).

No porosity was encountered during drilling of well.

A 65' core of 100% anhydrite was recovered from interval 3395'-3460'.

Due to low structural position of the well, it was abandoned with no further drilling.

Ran a Schlumberger Gamma-Ray Sonic Log.

Plug #1	3410'-3240'	170'	70	sq. of com. ce.
#2	3225'-3025'	200'	60	sq. of com. ce.
#3	1420'-1220'	200'	60	sq. of com. ce.
#4	350'-250'	100'	30	sq. of com. ce.
#5	25'-00'	25'	10	sq. of com. ce.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE **Owner & Operator**DATE **8-29-66**

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

APPROVED

*See Instructions on Reverse Side

SEP 1 1966

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.