

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0550543

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-

7. UNIT AGREEMENT NAME

Government "N" Con.

8. FARM OR LEASE NAME

-

9. WELL NO.

1-y

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

**All of Sections 19 & 30
Twp. 20S Rgs. 34E**

12. COUNTY OR PARISH

Lee County

13. STATE

New Mexico

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Cities Service Oil Company

3. ADDRESS OF OPERATOR

Box 69 - Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

660' FSL & 2083.9' FWL Sec. 19-20S-34E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3675' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3199 Anhydrite. Ran 96 3/4 joints (3176.82') 13 3/8" OD, 68#, 61#, 54.5#, and 48# H-40 and J-55 casing. Set at 3198.21'.

1st stage - Cemented w/650 sx Class C, 4% gel, 5# Gilsomite, 32# salt, 1% CaCL2 and 1/4# Floresal. Followed by 200 sx neat Class C, 1% CaCL2. Plug down @ 4:35 PM on 5-25-68. Opened DV tool set @ 1750' @ 4:50 PM. Circulated 150 sx cement to pit.

2nd stage - Cemented thru DV tool w/1100 sx Class C, 4% gel, 5# Gilsomite, 1% CaCL2 and 1/4# Floresal. Followed by 500 sx Class C, 4% gel, 5# Gilsomite, 32# salt and 1% CaCL2. Plug down @ 10:55 PM. Circulated 200 sx cement to pit. WOC 26 hrs. Tested 13 3/8" casing before drilling DV tool to 1000 psi for 30 minutes, held ok. Drilled DV tool. Tested 13 3/8" after drilling DV tool to 1000 psi for 30 minutes with no drop in pressure. Prepare to drill ahead.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE **District Clerk**

DATE **May 28, 1968**

(This space for Federal or State seal)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

DATE

MAY 31 1968

*See Instructions on Reverse Side
J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-685229
GPO 8 37-499 8 67-851

82 MA 02 11 11 11 11