STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

we, er comice acceives	
DISTRIBUTION	
SANTA PE	
FILE	
U.S.G.S.	
LAHO OFFICE	l
OPERATOR	

UIL CONSERVATION DIVISION

DISTRIBUTION	Р. О. ВС	Form C-103 - Revised 10-1-73			
SANTAFE	SANTA FE, NEV	1121.302.13.1.74			
FILE			Sa. Indicate Type of Leuse		
U.S.Q.S.	•		State X Fee		
LAND OFFICE			5. State Oil & Gas Lease No.		
OPERATOR			5. State on a day heave not		
			- immunimm		
SUNDRY N	IOTICES AND REPORTS OF	N WELLS			
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO CHILL ON TO DELPHIN OR PLUS SACE TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-1)11 FOR SUCH PROPOSALS.)					
1.			7. Unit Agreement Name		
OIL X GAS WELL	OTHER-				
Name of Operator			8, Farm or Lease Name		
Amoco Production Compan	ıv		State A-Z RA/A		
J. Address of Cherator	-3		9. Well No.		
P. O. Box 68 Hobbs, NM 88240			34		
			10. Field and Pool, or Wildcat		
4. Location of Well			11 1 5 5		
UNIT LETTER A 60	00 FEET FROM THE North	LINE AND	Water Seven Rivers		
THE East LINE, SECTION	9 township]	9-S RANGE 38-E HMPN			
	15. Elevation (Show whethe	er DF, RT, GR, etc.)	12. County		
		3620 RDB	LEA ())))))		
io. Check App	rapriate Box To Indicate	Nature of Notice, Report or O	ther Data		
NOTICE OF INTE	•	•	T REPORT OF:		
NOTICE OF INTE	NTION TO:	SUBSEQUEN	TREFORT OF.		
	. —	1			
PERFORM REMECIAL WORK	PLUG AND ABANDON		ALTERING CASING		
TEMPORARILY ABANDON		COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT (X)		
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB			
		OTHER			
OTHER]			
17. Describe Proposed or Completed Operat	too (Clarely styre all parties of	della and sina passinase datas is still its	a activated data of starting any proposed		
17. Describe Proposed of Completed Operat work) SEE RULE 1103.	ions (Grearry state are pertinent de	statis, and give pertinent dates, includin	g estimated date of starting any proposed		
	·				

Plugged and abandoned per the following procedure:

Ran a cement retainer set at 2204'. Squeezed perfs 3265'-3302' with 400 SX Class C cement. Perforated 9-5/8'' casing at 1300' with 4 JSPF. Ran a cement retainer set at 1250'. Squeezed with 500 SX Class C cement. Reversed out 20 SX. Load hole with mud laden fluid. Spotted a 20' cement surface plug. Erected permanent P X A marker. Will advise when location is ready for final inspection.

id, I hereb	by certify that the inform	stion above is true a	and complete to the be	at of my knowledge and be	itef.		
*16HED	306 NO	ws		Admin. Analyst	t	DATE5-19	-80
APPROVED	. feli Ita	tomui	YITCE	OIL & GÁD		DATE TE TO THE TENT OF	7.789
0+0	1-NMOCD, H	any: 1-Hou	1-Susp	1-BD			