

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-24082
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	A-1543-1
7. Lease Name or Unit Agreement Name	NORTH MONUMENT G/SA UNIT BLK. 3
8. Well No.	9
9. Pool name or Wildcat	WSW-SAN ANDRES

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☐ OTHER WATER SUPPLY WELL

2. Name of Operator
Amerada Hess Corporation

3. Address of Operator
P.O. DRAWER D, MONUMENT, NM 88265

4. Well Location
Unit Letter I : 1650 Feet From The SOUTH Line and 990 Feet From The EAST Line

Section 17 Township 19S Range 37E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

NMGSAU #309 (10-09-96 THRU 10-11-96)

PRIDE WELL SVC. MIRU. ND WATER SUPPLY LINE. UNFLANGED MASTER VALVE, ADAPTER FLANGE, RMV'D. REDA CABLE PACKING, & UNFLANGED TUBING HEAD W/REDA CABLE PACKOFF. NU BOP. RAN SANDLINE & FOUND FL INSIDE 5-1/2" @ 300' FR. SURF. RAN TBG. SUBS ON SANDLINE, SAT DWN. & OPENED DRAIN @ 1,953'. CABLE SVCS. & WEATHERFORD MIRU. TOH W/5-1/2" MMS X 8RD CSG. NIPPLE, 9 JTS. 5-1/2" 15.5# CSG. IPC-OD BARE, 20 JTS. 5-1/2" 14# CSG. IPC-OD BARE, 19 JTS. 5-1/2" 14# CSG. IPC-OD "NAP-WRAPPED", 5-1/2" 8RD DRAIN, 1 JT. 5-1/2" 14# CSG. IPC-OD "NAP-WRAPPED", 5-1/2" 8RD CHECK, 1 JT. 5-1/2" 14# CSG. IPC-OD "NAP-WRAPPED", PUMP, PROTECTOR, UPPERTANDEM MTR., & LOWER TANDEM MTR. NOTE: CABLE FOUND TO BE GOOD. FOUND PUMP HARD TO TURN. LOCATED 15 FAILURES IN SC-850 IPC COATING IN 5-1/2" CASING RANGING IN SIZE OF A DIME TO A QUARTER. PRIMARY FAILURE WAS
(CONTINUED)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Terry L. Harvey TITLE SR. STAFF ASSISTANT DATE 12/11/96

TYPE OR PRINT NAME TERRY L. HARVEY

TELEPHONE NO. 505-393-2144

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: