

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-1431
7. Unit Agreement Name
8. Farm or Lease Name State T
9. Well No. 8
10. Field and Pool, or Wildcat Eunice-Monument (G-SA)
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Drilling
2. Name of Operator Amerada Hess Corporation
3. Address of Operator Drawer "D", Monument, New Mexico 88265
4. Location of Well UNIT LETTER <u>K</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>25</u> TOWNSHIP <u>19S</u> RANGE <u>36E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3667' G.L.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Leatherwood Drilling Co. spudded 12½" hole at 9:30 P.M. 5-16-73.
Finished drilling 12½" hole to 1148' at 8:45 P.M. 5-18-73.
Ran 36 jts. of 9-5/8" OD 32.3 lbs. csg. set at 1148' and cemented w/530 sxs of class 'C' cement w/2% calcium chloride. Cement circulated. WOC 18 hrs. Tested csg. w/1000 lbs. for ½ hr. Started drilling 8-3/4" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Al Higuera</u>	TITLE <u>Drilling Supervisor</u>	DATE <u>5-23-73</u>
APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		