

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions
reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM 0149957	
2. NAME OF OPERATOR Llano, Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P.O. Box 1320, Hobbs, New Mexico 88240		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL and 2010' FEL of Section 18		8. FARM OR LEASE NAME Brooks Federal	
14. PERMIT NO.		9. WELL NO. 7	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3511.4 GL		10. FIELD AND POOL, OR WILDCAT Salt Lake Yates	
		11. SEC. T. R. M. OR BLK. AND SURVEY OR AREA 18, 20S, 33E, NMPM	
		12. COUNTY OR PARISH Lea	
		13. STATE NM	

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Liner Setting

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 4½", 9.5#, J-55 liner with top at 2608' and bottom 3034'. Cmtd w/75 sx Class C plus 0.5% Halad 22-A and 5#/sx KCL. Cmt circulated. Whirley Shoe on bottom and Texas Pattern Shoe on top.

Ran GR-CNL-Collar locator log.

Perf. 3010 - 3014, 3018 - 3022, 3026 - 3030 w/2JSPF plus one shot extra at bottom of each 4' interval. Acidized w/200 gals. 15% N.E. HCL, flushed w/2 Bbls form. H2O.

Prep to run potential test.

work started: 2-1-76

work completed: 2-5-76

TD 3034'

PBD 3031'

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Mgr. of Operations & Const.

DATE

February 9, 1976

(This space for Federal or State use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

FEB 19 1976

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side