

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

3-NMOCC  
1-File

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease

State ☐ Fee ☐

5. State Oil & Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO CLEAN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator <b>GETTY OIL COMPANY</b>	8. Farm or Lease Name <b>T. ANDERSON</b>
3. Address of Operator <b>P.O. BOX 249, HOBBS, NEW MEXICO 88240</b>	9. Well No. <b>4</b>
4. Location of Well UNIT LETTER <b>I</b> , <b>2223</b> FEET FROM THE <b>SOUTH</b> LINE AND <b>853</b> FEET FROM THE <b>EAST</b> LINE, SECTION <b>8</b> TOWNSHIP <b>20</b> RANGE <b>37</b> N.M.P.M.	10. Field and Pool, or Wildcat <b>UNDESIGNATED</b>
15. Elevation (Show whether DE, RT, GR, etc.) <b>3656.1 GR</b>	12. County <b>LEA</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

T.D. of 8-3/4" hole at 6957'. 7" casing previously set at 4924'. Set 5" 15# P 110 LT & C Liner at 6963'. Top of liner at 4693'. Cemented with 850 sacks Class H Cement. Reversed out estimated 320 sxs. Cement. Tested 5" Liner with 1500# for 30 minutes before and after drilling out cement. No drop in pressure.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY:

SIGNED **C. L. Wade:** **C. L. Wade**

TITLE **AREA SUPERINTENDENT**

DATE **10-7-76**

**Jerry Sexton**  
**Dist. & Supv.**

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

WLG/bh

**OCT 19 1976**

RECEIVED

Oct. 1-1978

OIL CONSERVATION COMM.  
LAWSON, W. M.