

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPL. E.  
(Other instructions on re-verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

*NM-18264*

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back into different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED  
JAN 5 1978  
U.S. GEOLOGICAL SURVEY  
HOUSTON, TEXAS

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

*Warrior, Inc.*

3. ADDRESS OF OPERATOR

*206 N. Main Midland, Texas 79701*

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

*NE/4 NE/4*

*990' FNL & 330' FEL*

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

*Federal D*

9. WELL NO.

*#12*

10. FIELD AND POOL, OR WILDCAT

*Eumont 7 Rivers Queen*

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

*27-20S-36E*

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

*3581 GR*

12. COUNTY OR PARISH

*Lea*

13. STATE

*New Mex.*

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

*Completion*

☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1.) *MIRU completion rig, & run GR/Neutron log from 4110' to 3000'.*

2.) *Perforate Penrose zone w/6(5/8" Jet holes) @ 4109', 4100', 4071',  
4065', 4061', & 4091.*

3.) *Spot 15 % acid thru 2 3/8" tubing with packer, pull & set packer @ 4000'.  
Acidize with 2000 gal. 15% NE acid using 10 ball sealers.*

4.) *Swab Back and test thru 2 3/8" tubing.*

5.) *If warranted fracture treat w/30,000 gal Versagel & 35,500# sand.*

6.) *Put well on beam pump and test.*

18. I hereby certify that the foregoing is true and correct

SIGNED

*J. A. Freeman*

TITLE *Petroleum Engineer*

DATE *1-3-78*

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

\*See Instructions on Reverse Side

APPROVED

JAN 6 1978

*Simardo O. Lopez*  
ACTING DISTRICT ENGINEER

APPROVE

10-10-10  
10-10-10  
10-10-10