

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
P.O. Drawer "A", Levelland, Texas 79336

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 840 FNL & 2080 FEL, Sec 24
AT TOP PROD. INTERVAL: (Unit B NW $\frac{1}{4}$, NE $\frac{1}{4}$)
AT TOTAL DEPTH:

5. LEASE
LC-031736 (a) ✓

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Gillully "A" Federal

9. WELL NO.
16 ✓

10. FIELD OR WILDCAT NAME
Eunice-Monument (Grayburg)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
24-20-36 ✓

12. COUNTY OR PARISH
Lea

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3536.6 GR

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Spud & Casing Test <input checked="" type="checkbox"/>	X <input checked="" type="checkbox"/>

RECEIVED

DEC 8 1978

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U.S. GEOLOGICAL SURVEY

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 11-30-78, Capitan (rig #20) spudded a 12 1/4" hole at 4:00 p.m. Drilled to TD 1045' and ran 8 5/8" 24# K-55 ST & C casing set at 1045'. Cemented with 325 sx LIGHT and 100 sx Class C plus 2% CACL. Circulated 45 sx. PD 10:15 p.m. 11-2-78. WOC 18 hours. Test casing 1000# for 30 minutes. Test O.K. Reduced hole to 7 7/8" and resumed drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dennis Evans TITLE Asst. Admin. Analyst DATE 12-6-78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

- CONDITIONS OF APPROVAL, IF ANY:
- 0+4-USGS -H
 - 1-Houston
 - 1-Susp
 - 1-DE

ACCEPTED FOR RECORD
DEC 8 1978
J. S. GEOLOGICAL SURVEY
HOBS, NEW MEXICO

*See Instructions on Reverse Side