

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240DISTRICT II
P.O. Drawer DD, Artesia, NM 88210DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-26169
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 81428
7. Lease Name or Unit Agreement Name STATE U GAS COM
8. Well No. 2
9. Pool name or Wildcat EUMONT Yates SR-RW

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator

AMERADA HESS CORPORATION

000495

3. Address of Operator

DRAWER D, MONUMENT, NM 88265

4. Well Location

Unit Letter C : 990 Feet From The NORTH Line and 2160 Feet From The WEST Line

Section 32

Township 19S

Range 37E

NMPM LEA

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐CHANGE PLANS ☐PULL OR ALTER CASING ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐CASING TEST AND CEMENT JOB ☐OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-12 THRU 10-18-93

MIRU DA&S WELL SER. INSTALLED BOP AND TOH WITH 111 JTS. 2-3/8" TBG. TIH WITH 4-3/4" BOTTOM BIT, AND TAGGED FILL IN OH AT 3,492'. RIGGED UP TRI-CONE AIR DRILLING EQUIPMENT. CLEANED OUT FILL FROM 3,492' TO 3,500' AND DRILLED FORMATION FROM 3,500' TO 3,575'. CIRC. AIR FOR 45 MIN. TO CLEAN HOLE. TOH W/BIT. TIH WITH RBP ON 20 JTS. 2-3/8" TBG. & SET AT 639'. COULD NOT BACK WELLHEAD OFF. FILLED CASING WITH WATER AND HEATED WELLHEAD. BROKE WELLHEAD OFF AND INSTALLED NATIONAL WELLHEAD THAT WILL ACCEPT T-16 WRAP AROUND. TIH WITH 20 JTS. TBG. AND SWABBED BACK WATER. TOH WITH BP. TIH WITH NOTCHED CPLG., SN, AND 113 JTS. 2-3/8" TBG. SET AT 3,543' WITH CLOSED IN DISC IN NOTCHED CPLG. HOOKED UP WELLHEAD. TIH WITH SINKER BAR AND RUPTURED CLOSED IN DISC. RD PULLING UNIT, CLEANED LOCATION & RESUMED PROD. WELL.

TEST OF 10-22-93 - 209 MCFPD IN 24 hrs.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

R. L. Wheeler, Jr.

TITLE SUPV. ADMIN. SER.

DATE 11-22-93

TYPE OR PRINT NAME R.L. WHEELER, JR.

(505)

TELEPHONE NO 393-2144

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEC 06 1993