

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	TRUE VERTICAL DEPTH FEET	VERTICAL SECTION FEET	R E C T A N G U L A R C O O R D I N A T E S FEET	DOG LEG SEVERITY DEG/100FT
3000.	1 0	N 78 E	2999.64	-29.57	15.66 S	0.4
3100.	0 45	N 77 E	3099.63	-30.98	15.33 S	0.3
3200.	0 45	N 33 E	3199.62	-31.88	14.60 S	0.6
3300.	1 0	N 33 E	3299.60	-32.48	13.32 S	0.3
3400.	1 0	N 48 E	3399.59	-33.37	12.00 S	0.3
3500.	1 0	N 50 E	3499.57	-34.47	10.85 S	0.0
3600.	0 30	N 38 E	3599.56	-35.20	9.91 S	0.5
3700.	0 30	N 21 E	3699.56	-35.50	9.15 S	0.1
3800.	0 30	N 24 E	3799.56	-35.69	8.35 S	0.0
3900.	1 0	N 44 E	3899.55	-36.22	7.27 S	0.6
4000.	0 45	N 65 E	3999.53	-37.29	6.39 S	0.4
4100.	0 30	N 67 E	4099.53	-38.19	5.94 S	0.3
4200.	0 45	N 39 E	4199.52	-38.93	5.29 S	0.4
4300.	0 45	N 36 E	4299.51	-39.54	4.25 S	0.0
4400.	0 45	N 47 E	4399.50	-40.22	3.28 S	0.1
4500.	0 30	N 60 E	4499.50	-40.97	2.63 S	0.3
4600.	0 30	N 30 E	4599.49	-41.47	2.02 S	0.3
4700.	0 45	N 16 E	4699.49	-41.72	1.02 S	0.3
4800.	0 30	N 23 E	4799.48	-41.90	0.01 N	0.3
4900.	0 45	N 51 E	4899.47	-42.39	0.87 N	0.4
5000.	0 30	N 27 E	4999.47	-42.92	1.71 N	0.4
5100.	0 30	N 12 E	5099.46	-43.06	2.53 N	0.1
5200.	0 15	N 19 E	5199.46	-43.13	3.16 N	0.3
5227.	0 45	N 4 W	5226.46	-43.12	3.40 N	2.0
5321.	1 0	N 5 W	5320.45	-42.76	4.83 N	0.3
5415.	1 15	N 15 W	5414.43	-42.13	6.64 N	0.3
5509.	1 0	N 16 W	5508.41	-41.34	8.42 N	0.3
5603.	1 0	N 12 W	5602.39	-40.68	10.01 N	0.1
5697.	1 15	N 2 E	5696.38	-40.21	11.85 N	0.4
5791.	1 0	N 14 W	5790.36	-39.70	13.68 N	0.4