

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIP  
(Other instruction  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-9993

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Treat "LI" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 25-20S-33E  
Unit N MMPM

12. COUNTY OR PARISH

Lea

13. STATE

NM

1. OIL WELL  GAS WELL  OTHER

2. NAME OF OPERATOR  
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR  
207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

990' FSL & 1650' FWL of Sec. 25-20S-33E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3664' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Set Conductor pipe, spudded

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded a 12 1/4" hole at 6:30 PM 7-30-79.

Rat hole digger set 40' of conductor pipe w/4 yards of Ready-Mix.

TD 1425' - Ran 36 joints of 8-5/8" 24# J-55 (1441') of casing set at 1425'. 1-guide shoe at 1425' and insert float at 1385'. Cemented w/350 sacks of Halliburton Lite, 1/4# flocele, 5# gilsonite, 2% CaCl. Followed w/200 sacks of Class C 2% CaCl. PD 11:00 PM 8-3-79. Cement circulated 50 sacks to surface. WOC 18 hours. Nipped up and tested to 1000#. OK. Reduced hole to 7-7/8", drilled plug and tested to 600#. OK. Resumed drilling.

RECEIVED

AUG 17 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Christine Tomlinson*

TITLE

Geol. Secty

DATE

8-16-79

(This space for Federal or State-office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

AUG 16 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side

RECEIVED

AUG 21 1973

RECEIVED O.C.D. HOBBS, OFFICE

AUG 21 1973

O.C.D. HOBBS, OFFICE