

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Drilling well		5. LEASE DESIGNATION AND SERIAL NO. NM 33955
2. NAME OF OPERATOR DAVID FASKEN		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 608 First National Bank Building, Midland, Texas 79701		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface		8. FARM OR LEASE NAME Baetz "23"
14. PERMIT NO. 1980' FSL & 1980' FWL		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3564' KB		10. FIELD AND POOL, OR WILDCAT Wildcat
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 23, T-20-S, R-32-E
		12. COUNTY OR PARISH Lea
		13. STATE New Mexico

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

## SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐WATER SHUT-OFF ☐REPAIRING WELL ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOT OR ACIDIZE ☐ABANDON\* ☐SHOOTING OR ACIDIZING ☐ABANDONMENT\* ☐REPAIR WELL ☐CHANGE PLANS ☐(Other) Run & Cmt 13-3/8" csg ☒(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-18-79 TD 2990' in anhydrite. Ran 29 jts (1101.97') 13-3/8", K-55, 61#/ft, ST&C & 44 jts (1897.69') 13-3/8", K-55, 54.5#/ft, ST&C casing set @ 2990', cemented w/2000 sx Halliburton-Lite w/15# salt & 1/4# flocele/sk (S.W. 12.7#/gal, w/yield 1.40 cu ft/sk), plug down @ 9:30 p.m. 8-18-79, cement circulated to surface.

8-19-79 NU well-head &amp; BOP's, WOC 30 hrs.

8-20-79 Tested BOP's &amp; casing to 1500 psig for 30 mins. Drilling ahead 12 1/4" hole.

18. I hereby certify that the foregoing is true and correct

SIGNER

Robert H. Angevine

TITLE Agent

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE 8-21-79

AUG 21 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

RECEIVED

AUG 23 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO