

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Drilling well		5. LEASE DESIGNATION AND SERIAL NO. NM 33955
2. NAME OF OPERATOR DAVID FASKEN		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 608 First National Bank Building, Midland, Texas 79701		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface  1980' FSL & 1980' FWL		8. FARM OR LEASE NAME Baetz "23"
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3564' KB	9. WELL NO. 1
		10. FIELD AND POOL, OR WILDCAT Wildcat
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 23, T-20-S, R-32-E
		12. COUNTY OR PARISH Lea
		13. STATE New Mexico

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Run &amp; Cmt 20" csg

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 8-3-79 Spudded 26" hole @ 10:30 a.m., drilling w/red bed mud.
- 8-11-79 TD 1115', ran 27 jts, 20", K-55, 133#/ft, ST&C casing set @ 1115' & cemented w/1340 sx Class "C" cement (S.W. 14.1-14.8#/gal w/yield 1.50-1.32 cu ft/sk), plug down @ 6:15 a.m. 8-12-79--cement circulated to surface. Top Rustler Anhydrite 1065' (+2499'). WOC 23 hrs.
- 8-13-79 Drilling 17½" hole w/10.0 PPG brine.

RECEIVED

AUG 23 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

## 18. I hereby certify that the foregoing is true and correct

SIGNED

Robert H. Angevine

TITLE Agent

DATE 8-21-79

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

AUG 25 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO